## **Scissor Lift Certification Cambridge**

Scissor Lift Certification Cambridge - Numerous worksites and tradespeople like for example welders, masons and iron workers use scissor lift platforms to be able to help them reach elevated work areas. The utilization of a scissor lift is often secondary to their trade. Hence, it is essential that all operators of these platforms be trained properly and licensed. Regulators, industry and lift manufacturers work together in order to make certain that operators are trained in the safe use of work platforms.

Scissor lift work platforms are likewise known as manlifts or AWPs. These work equipment are somewhat easy to use and provide a stable work surroundings, nonetheless they do have risks as they raise people to heights. The following are several key safety issues common to AWPs:

There is a minimum safe approach distance (MSAD) for all platforms so as to protect from accidental power discharge due to proximity to power lines and wires. Voltage could arc across the air and cause injury to staff on a work platform if MSAD is not observed.

Caution must be taken when the work platform is lowered to guarantee stability. The boom must be retracted, moving the load toward the turntable. This would help maintain stability during lowering of the platform.

Regulations do not mandate those working on a scissor lift to tie off. However, staff may be required to tie off if required by employer guidelines, local regulations or job-specific risk assessment. The manufacturer-provided anchorage is the only safe anchorage to which harness and lanyard combinations must be attached.

Observe the maximum slope rating and do not exceed it. A grade can be measured by laying a board or straight edge on the slope. Then, a carpenter's level can be placed on the straight edge and raised until the end is level. By measuring the distance to the ground and dividing the rise by the length of the straight edge, then multiplying by 100, you can determine the percent slope.

A typical walk-around check needs to be done to determine if the unit is mechanically safe. A location assessment determines if the work area is safe. This is important specially on changing construction sites due to the risk of obstacles, unimproved surfaces, and contact with power lines. A function test should be done. If the unit is used safely and correctly and proper shutdown procedures are followed, the risks of accidents are really lessened.